

# ENERGY CONTROL PROCEDURE

The following Energy Control Procedure should be used for the equipment listed below.

Date Written: 3-27-00 Date of Revisions: 4-25-12 - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_

Authors: Steve Vol

Reviewing Personnel: FRANK REPROGLE Date Reviewed: \_\_\_\_\_

Approvals: FRANK REPROGLE Date Approved: \_\_\_\_\_

## EQUIPMENT DESCRIPTION

GENERAL DESCRIPTION: COE portable reel BMC # (3045)

MANUFACTURER: COE

MODEL: CPR-6027 SERIAL NUMBER: 7182-2

LOCATION: Production

## CONTROLS

The following Controls, including "start/stop" buttons, toggle switches, emergency stop button, shut-off valves, etc. have been identified for this equipment.

Description of Control	Location on Equipment
Start/stop toggle switch	Control box lower right
Breaker switch	Control box upper left
Main electrical disconnect	Side of reel
480 volt plug	Coming out of main disconnect

**ENERGY SOURCES/ISOLATION DEVICES**

The following Energy Sources and Energy Isolation Devices supporting this equipment have been identified.

Energy Types: (CHECK ALL THOSE APPLICABLE)

Electrical	x
Pneumatic	
Hydraulic	
Steam	
Chemical	
Thermal	
“Stored” Energy	
Other	

Sources / Devices	Location	Type of Lock/Tag Needed
Start / stop toggle switch	Control box lower right	NA
Breaker switch	Control box upper left	NA
Main disconnect	Side of reel	Standard lock & tag
480 volt plug	Coming out of main disconnect	Standard lock, tag, lock out cover



**RELEASE AND RESTART PROCEDURES**

The steps listed below must be followed to properly release this equipment from a locked or tagged out condition and restart it.

<b><u>Procedure</u></b>	<b><u>Location</u></b>
Inspect work area and remove tools and other non-essential items.	
Inspect equipment and components to make sure it is intact and ready to run.	
Notify "affected" and "other" employees in the area of impending restart and make sure they are safely positioned away from the equipment	
Plug in 480 volt	Coming out of main disconnect
Turn on main disconnect	Side of reel
Toggle start/stop switch to start	Control box lower right